




E-6351




Ściągacz śrubowy DIN 1480 typ: oko - oko

Materiał : kute ze stali
 Standard : DIN 1480
 Wykończenie : ocynk galwaniczny
 Atesty : atest 2.1

średnica gwintu	dług. poz. zamkn.	dług. poz. o otwar.	dług. bez śrub	dług. całkowity	dług. thread	średnica oka zewn.	średnica oka wewn.	waga szt.
a	b	c	d	e	f	g	h	kg
mm	mm	mm	mm	mm	mm	mm	mm	
5	114	170	70	57	35	16	8	0.07
6	160	246	110	80	55	20	9	0.11
8	168	248	110	84	57	22	10	0.2
10	210	300	125	105	68	31	14	0.28
12	222	305	125	110	70	35	16	0.43
14	244	334	140	123	75	40	18	0.61
16	300	416	170	143	88	47	22	1
20	334	466	200	165	105	52	24	1.6
22	372	527	220	185	118	60	27	2.2
24	410	587	255	208	135	65	27	2.8
30	440	605	255	220	135	71	31	4.1
33	490	690	295	245	148	88	36	6
36	554	740	295	277	158	94	38	8.5
42	600	800	330	300	170	110	49	11



E-6352



Ściągacz śrubowy DIN 1480 typ: hak - hak

Materiał : kute ze stali
 Standard : DIN 1480
 Wykończenie : ocynk galwaniczny
 Atesty : atest 2.1

średnica gwintu	długość poz. zamkn.	długość poz. otwartej	długość bez śrub	długość całkowita	długość gwintu	rozstaw hak	grubość haka	waga szt.
a	b	c	d	e	f	g	h	kg
mm	mm	mm	mm	mm	mm	mm	mm	
6	184	270	110	92	55	8	15	0.11
8	200	280	110	100	57	10.5	15	0.2
10	234	323	125	117	68	13	11	0.28
12	260	343	125	130	70	16	13	0.43
14	278	368	140	139	75	18	15	0.61
16	322	438	170	161	88	20	17	1
20	382	514	200	191	105	21	21	1.6
22	456	601	220	228	118	24	28	2.2
24	496	673	255	248	135	26	33	2.8
30	550	715	255	275	135	34	35	4.1
33	600	799	295	300	148	38	40	6
36	640	825	295	320	158	46	45	8.3