



# Green Pin® Lifting Eye S/S-GR5

## Grade 5 stainless steel lifting eye

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup> CE

working load limit	diameter thread	diameter base	diameter eye outside	diameter eye inside	length	thickness base	diameter	weight each
					e	f	g	kg



• Cer

working load limit	thread	a	b	c	d	e	f	g	h	weight each
t	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
0.2	M8 x 1.25	20	34	27	27	27	14	14	14	0.12
0.4	M10 x 1.50	20	38	30	30	30	16	16	16	0.25
0.6	M12 x 1.75	25	47	37	37	37	20	20	20	0.45
0.8	M14 x 2.00	30	57	44	44	44	24	24	24	0.75
1	M16 x 2.00	36	63	49	49	49	28	28	28	1.10
1.5	M18 x 2.50	36	63	49	49	49	31	31	31	1.65
2	M20 x 2.50	40	72	56	56	56	34	34	34	2.20
2.5	M22 x 2.50	42	82	63	63	63	36	36	36	2.75
3	M24 x 3.00	55	95	74	74	74	40	40	40	3.30

ALDINI