





Thimbles

Generally to EN 13411-1

- **Material:** mild steel
- **Standard:** generally to EN 13411-1 formerly BS 464
- **Finish:** hot dipped galvanized
- **Certification:** 2.1



G-6170



diameter rope		width groove	length	length inside	width inside	thickness back	weight per 100 pcs
inch	mm	a mm	b mm	c mm	d mm	e mm	kg
3/16	5	5.5	44	28	19	3	3.5
1/4	7	6	48	30	20	3.5	2.8
5/16	8	8	54	33	22	4	5.7
3/8	10	10	64	38	25	4.8	8
7/16	11	13	73	41	29	4.8	14.2
1/2	13	14	80	44	32	5.6	18
9/16	15	15	80	44	32	5.6	18.9
5/8	16	17	98	59	41	7.9	22.4
11/16	17	19	108	67	44	7.9	39.7
3/4	19	20	124	73	51	9.5	45.6
13/16	21	21	124	73	51	9.5	62.4
7/8	22	23	133	83	57	9.5	61.5
15/16	24	25	146	92	64	10.3	106
1	25	27	162	108	70	10.3	97.3
1 1/8	28	29	178	111	76	12.7	151
1 1/4	32	33	197	133	95	12.7	204
1 3/8	35	38	229	152	105	15.9	318
1 1/2	38	41	254	165	114	17.5	363
1 5/8	42	46	254	165	114	17.5	499
1 3/4	45	51	286	178	127	25.4	556
1 7/8	47	60	318	191	133	28.6	-
2	50	64	330	203	140	28.6	-
2 1/8	54	64	330	203	140	28.6	-
2 1/4	57	67	356	216	146	30.2	-
2 1/2	65	70	413	241	159	31.8	-
2 3/4	70	86	502	273	203	41.3	-