

## Green Pin® Heavy Duty Dee Shackle BN

### High load capacity dee shackle with safety bolt

- **Material:** bow and pin alloy steel, grade 8 quenched and tempered
- **Safety Factor:** MBL equals 5 x WLL
- **Standard:** ASME B30.26
- **Finish:** hot dipped galvanized
- **Certification:** [2.1](#) [2.2](#) [3.1](#) [MTC<sup>a</sup>](#) [MPI<sup>a</sup>](#) [US<sup>a</sup>](#) [CE](#)

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	thickness nut	weight each
t	a	b	c	d	e	f	g	h	i	kg
	mm	mm	mm	mm	mm	mm	mm	mm	mm	
120	95	95	208	95	147	274	521	453	50	110

In inch

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	thickness nut	weight each
t	a	b	c	d	e	f	g	h	i	lbs
	inch	inch	inch	inch	inch	inch	inch	inch	inch	
120	3 <sup>3</sup> / <sub>4</sub>	3 <sup>3</sup> / <sub>4</sub>	8 <sup>3</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>4</sub>	5 <sup>25</sup> / <sub>32</sub>	10 <sup>25</sup> / <sub>32</sub>	20 <sup>1</sup> / <sub>2</sub>	17 <sup>27</sup> / <sub>32</sub>	1 <sup>31</sup> / <sub>32</sub>	243

CAD