



C



P-6810



DNV GL Master Link

- **Material:** alloy steel, grade 8
- **Safety Factor:** MBL equals 5 x WLL
- **Standard:** DNV 2.7-1, EN 12079-2 and EN 1677-4
- **Finish:** painted orange
- **Temperature range:** -20°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MTC³ DNV GL 2.7-1³

working load limit	diameter	length inside	width inside	weight each
t	a mm	b mm	c mm	kg
4.1	16	150	75	0.72
5.8	22	270	140	2.3
8.83	26	270	140	3.3
14.5	28	200	110	3
14.5	28	270	140	3.8
17.1	32	270	140	5.1
23.0	36	270	140	6.5
28.1	40	280	155	8.5
38.3	45	320	175	12.2
45	50	350	195	16.6
75	65	410	220	33.2
100	75	450	250	49.3

In inch

working load limit	diameter	length inside	width inside	weight each
t	a inch	b inch	c inch	lbs
4.1	$\frac{5}{8}$	$5 \frac{29}{32}$	$2 \frac{15}{16}$	1.59
5.8	$\frac{7}{8}$	$10 \frac{5}{8}$	$5 \frac{1}{2}$	5.07
8.83	$1 \frac{1}{32}$	$10 \frac{5}{8}$	$5 \frac{1}{2}$	7.28
14.5	$1 \frac{3}{32}$	$7 \frac{7}{8}$	$4 \frac{1}{2}$	6.61
14.5	$1 \frac{3}{32}$	$10 \frac{5}{8}$	$5 \frac{16}{32}$	8.38
17.1	$1 \frac{1}{4}$	$10 \frac{5}{8}$	$5 \frac{1}{2}$	11.24
23.0	$1 \frac{13}{32}$	$10 \frac{5}{8}$	$5 \frac{1}{2}$	14.33
28.1	$1 \frac{9}{16}$	$11 \frac{1}{32}$	$6 \frac{3}{32}$	18.74
38.3	$1 \frac{25}{32}$	$12 \frac{19}{32}$	$6 \frac{7}{8}$	26.9
45	$1 \frac{31}{32}$	$13 \frac{25}{32}$	$7 \frac{11}{16}$	36.6
75	$2 \frac{1}{2}$	$16 \frac{5}{32}$	$8 \frac{21}{32}$	73.19
100	$2 \frac{15}{16}$	$17 \frac{23}{32}$	$9 \frac{27}{32}$	108.69

